


LightSync™ Hub Details



LightSync 20-port Hub (shown in optional enclosure with transformer)

General

- 20-port hub to home run LightSync devices
- Provides power for up to 20 LightSync devices
- 20- LightSync RJ45 device inputs
- 20- LightSync RJ45 device outputs
- Resides on LightMaster LightSync data line
- UL Listed
- FCC approval for commercial use

Characteristics

- Contacts: SPST Maintained
- Termination: standard screw terminals
- Screw-actuated clamps for use with #18 AWG solid or stranded wire
- LightSync data line addressable

Physical:

- Mounts in controller or remotely

Electrical:

- Requires 24VAC transformer

Capacities:

- 20- LightSync RJ45 device inputs
- 20- LightSync RJ45 device outputs

Operating Environment:

- Location Interior Space
- Operating Temperature 0° to 60° C (32° to 140° F)
- Relative Humidity 10% to 95%
- Atmosphere Non-condensing, Non-explosive, Non-corrosive
- Vibration Stationary application, NEMA Level A



Energy Saving Lighting Controls

INTELLIGENT LIGHTING CONTROLS, INC.

5229 Edina Industrial Boulevard
 Minneapolis, Minnesota 55439
 Phone 952 829 1900
 FAX 952 829 1901
 www.ilc-usa.com

PD0607_revA